



Pressure, Level & Temperature Transmitters & Transducers

U.K. Distributor; Interface Force Measurements

Tel. 01344 776666 • Fax. 01344 774765

e-mail info@interface.uk.com •

www.interface.uk.com

EXTREME HIGH TEMPERATURE TRANSDUCER

Model 7770

Designed for the tough challenges and environmental rigors of space propulsion and aviation pressure testing.

FEATURES:

- +70°F to + 700°F standard medium
- High accuracy, 3% FSO standard (1% available)
- Lightweight, 8 ounces
- Hydrogen and LOX compatibility
- Custom probe lengths, 1.55" standard
- Designed to meet vibration and shock per MIL-STD-810
- 2 second time response for temperature, 0.5 sec optional
- 100 ohm platinum RTD standard

Typical Applications:


- High Vibration Environments
- Extreme or Harsh Environments
- Manifolds, Propulsion Systems
- Military and Defense Applications



All GP:50 Aerospace pressure transducers are manufactured and tested to the following MIL-STD and MIL-Spec standards to insure the highest quality assurance:

- NIST Traceability and Calibration..... MIL-STD-45662A
- Workmanship J-001 / NASA 8739.3 standards
- Quality System ISO 9001:2008

Designed to: MIL-STD-810 C&E
MIL-STD-461/462 D&E



WIRING CODE

	4-20 mA PIN OUT	Vdc PIN OUT
A	+ EXC./SIGNAL OUT	+ EXC.
B	NC	+SIGNAL OUT
C	NC	-SIGNAL OUT
D	- EXC./SIGNAL OUT	- EXC.
E	SHUNT OPTION	SHUNT OPTION
F	SHUNT OPTION	SHUNT OPTION

A5SL-7770.00 Rev A

GP:50 reserves the right to make product improvements and amendments to the product specifications stated throughout this brochure without prior notification. Please contact the factory on all critical dimensions and specifications for verification.



Pressure, Level & Temperature Transmitters & Transducers

U.K. Distributor; Interface Force Measurements

Tel. 01344 776666 • Fax. 01344 774765

e-mail info@interface.uk.com •

www.interface.uk.com

Specifications and options reflect standard product, other improved performance / mechanical / electrical / options available, consult factory for more information. Modifications may alter specs.

Ranges	+70°F to +700°F/ +20°C to +370°C
FS Output	3 mV/V at 10 Vdc / 0-5 Vdc / 4-20 dcmA / Isolated ptions
Temperature Sensor	100 ohm 2 wire platinum RTD standard 1000 ohm 2 wire platinum RTD optional
Excitation or Input Voltage Reverse Polarity Protected	18 to 36 Vdc
Static Accuracy	3% FSO 1% optional
Weight	8 oz. (approx.)
Electrical Connector	MIL PTIH-10-6P, D38999 series III optional
Response Time	2 seconds, (0.5 sec optional)
Meets MIL-STD-461/462 EMI/RFI	Some options will affect EMI/RFI rating
Flex Tubing	18" Armored Capillary Tube
System Pressure	Designed for up to 2000 psi sytem pressure.

ORDERING GUIDE:

Some options will affect dimensions, consult factory if important.
Use the following codes to identify desired item.

MODEL	OUTPUT	OPTIONS
● —	● —	●

Example: 7770-2-CA/FD/GH

OUTPUT

- 2 0-5 Vdc 4 wire hookup
- 3 4-20 dcmA
- 4 0-5 Vdc Isolated
- 5 0-10 Vdc 4 wire hookup
- 6 0-10 Vdc Isolated
- 9 0-5 Vdc 3 wire hookup
- 10 0-10 Vdc 3 wire hookup

OPTIONS

CONNECTORS

- CA PTIH-10-6P Bendix
- CI D38999/27YB98N
- DB D38999/27YA35PN

PORTS

- FD MS33656-4, 7/16-20 (M)

MISC:

- D Improved Static Accuracy to 1%
- GB Alternate Full Scale Outputs
- GH 100% Internal Shunt
- GL Cleaning for oxygen service
- JB 1000 ohm 2 wire RTD
- ME Shunt Cal, 80% Internal
- QV Improved response time to 0.5 seconds

FLEX TUBING:

- GT 30" Armored Capillary Tube
- HS 9" Armored Capillary Tube
- HV 24" Armored Capillary Tube
- HY 12" Armored Capillary Tube
- MT Non-standard Armored Capillary Tube (50" max)