



Pressure, Level & Temperature Transmitters & Transducers

U.K Distributor. Interface Force Measurements

Tel. 01344 77666 • Fax 01344 774765

info@interface.uk.com • www.interface.uk.com

DUAL TEMPERATURE & PRESSURE TRANSDUCER

Model 7880

Designed for the tough challenges and environmental rigors of space propulsion and aviation pressure testing.

FEATURES:

- High accuracy, 0.3% RSS standard (0.1% available)
- -100°F to +250°F standard medium
- Lightweight, 8 ounces
- Hydrogen and LOX compatibility
- Custom probe lengths, 1.55" standard
- Designed to meet vibration and shock per MIL-STD-810
- 2 second time response for temperature, 0.5 sec optional
- 100 ohm platinum RTD standard

Typical Applications:

- High Vibration Environments
- Manifolds, Propulsion Systems
- Military and Defense Applications

Heritage Includes:

- NASA
- Lockheed Martin
- EELV
- Johns Hopkins
- Shuttle Upgrade
- Boeing
- TRW-ABL
- Arkin Industries
- United Defense





All GP:50 Aerospace pressure transducers are manufactured and tested to the following MIL-STD and MIL-Spec standards to insure the highest quality assurance:

- NIST Traceability and Calibration..... MIL-STD-45662A
- Workmanship J-001 / NASA 8739.3 standards
- Quality System ISO 9001:2008

Designed to: MIL-STD-810 C&E
MIL-STD-461/462 D&E

Units are in inches



WIRING CODE

	4-20 mA PIN OUT	Vdc PIN OUT
A	+ EXC./SIGNAL OUT	+ EXC.
B	NC	+SIGNAL OUT
C	NC	-SIGNAL OUT
D	- EXC./SIGNAL OUT	- EXC.
E	SHUNT OPTION	SHUNT OPTION
F	SHUNT OPTION	SHUNT OPTION

A5SL-7880.00 Rev B

GP:50 reserves the right to make product improvements and amendments to the product specifications stated throughout this brochure without prior notification. Please contact the factory on all critical dimensions and specifications for verification.



Pressure, Level & Temperature Transmitters & Transducers

U.K Distributor. Interface Force Measurements

Tel. 01344 77666 • Fax 01344 774765

info@interface.uk.com • www.interface.uk.com

Specifications and options reflect standard product, other improved performance / mechanical / electrical / options available, consult factory for more information. Modifications may alter specs.

Ranges	15 thru 15,000 PSIA, PSIG or PSISG options
FS Output at Rated Pressure	0-5 Vdc / 4-20 dcmA / Isolated ptions
Temperature Output	100 ohm 2 wire platinum RTD standard 1000 ohm 2 wire platinum RTD optional
Excitation or Input Voltage Reverse Polarity Protected	18 to 36 Vdc
Non-Repeatability	<0.1% FSO
Non-Linearity	<0.2% FSO
Hysteresis	<0.2% FSO
Static Accuracy RSS (Pressure)	<0.3% FSO RSS, 0.1% optional
Static Accuracy (Temperature)	3% FSO, 1% optional
Pressure Medium (Wetted Materials)	316SS (Inconel, Hatelloy, Monel optional)
Operating/Environmental Temperature	-100°F to +250°F / -75°C to +120°C
Weight	8 oz. (approx.)
Electrical Connector	MIL PTIH-10-6P, D38999 series III
Response Time	< 4ms pressure, 2 seconds for temperature (0.5 sec optional)
Meets MIL-STD-461/462 EMI/RFI	Some options will affect EMI/RFI rating

ORDERING GUIDE:

Some options will affect dimensions, consult factory if important.
Use the following codes to identify desired item.

MODEL	OUTPUT	RANGE	PRESSURE TYPE	OPTIONS
●	—	●	—	●

Example: 7880-2-RH-G-CA/FD/GH

OUTPUT

- 2 0-5 Vdc 4 wire hookup
- 3 4-20 dcmA
- 4 0-5 Vdc Isolated
- 5 0-10 Vdc 4 wire hookup
- 6 0-10 Vdc Isolated
- 9 0-5 Vdc 3 wire hookup
- 10 0-10 Vdc 3 wire hookup

RANGE (PSI)

- PP 0-15 RK 0-750
- PR 0-20 RM 0-1000
- PO 0-25 RO 0-1500
- PV 0-50 RR 0-2000
- PZ 0-100 RT 0-3,000
- RB 0-150 RV 0-5,000
- RD 0-200 RX 0-7,500
- RF 0-300 RZ 0-10,000
- RH 0-500 SB 0-15,000

Contact factory for non-standard pressure ranges.

PRESSURE TYPE

- A Sealed Absolute, ref to vacuum
- G Gauge, ref to atmosphere
- SG Sealed Gauge, ref to 14.7 psia

OPTIONS

CONNECTORS

- CA PTIH-10-6P Bendix
- CI D38999/27YB98N
- DB D38999/27YA35PN

PORTS

- FA MS33649-4, 7/16-20 (F)
- FD MS33656-4, 7/16-20 (M)

MISC:

- D Improved Accuracy to 0.1% Pressure, and 1% Temperature
- GB Alternate Full Scale Outputs
- GH 100% Internal Shunt
- GK Inconel Pressure Cavity
- GL Cleaning for oxygen service
- GP Hastelloy Pressure Cavity
- QU Monel Pressure Cavity
- JB 1000 ohm 2 wire RTD
- ME Shunt Cal, 80% Internal
- QV Improved response time to 0.5 seconds