

SUBMERSIBLE LEVEL TRANSMITTER

MODEL 313L



Model 313L
Submersible Level Transmitter

FEATURES:

- Available ranges of 0-20" WC thru 300 PSI (50 MBAR to 21 BAR)
- Case rated to 900 feet WC (275 meters WC)
- Up to $\pm 0.10\%$ FSO accuracy
- 316L stainless steel housing with optional titanium
- Hytrel jacketed cable with optional Tefzel®
- Lightning suppression as standard

APPLICATIONS:

- Wet wells, ponds, rivers and tank level measurements
- Water treatment
- Ground water monitoring
- Dredging levels
- Shipboard level control

PRODUCT OVERVIEW:

The Model 313L from GP:50 is a line of highly accurate and reliable submersible level transmitters. The corrosion-resistant 316L stainless steel construction, and an integrated hydrophobic breather vent help provide years of maintenance-free service.

FIELD OPTIONS:

- Slim 0.69" (1.74 cm) diameter (Model 313S)
- Titanium construction (Model 313L-NI)
- Additional Hytrel cable and Tefzel® jacketed cable lengths
- Tapered inlet with stand-off plate for wastewater
- Remote zero and span adjustments


GP:50 MODEL 313L

DIMENSIONAL DRAWING

All dimensions are in inches (mm)

STANDARD WIRING

WIRE	MODEL 313L
RED	+EXC/SIG
BLK	-EXC/SIG
GRN	N/C
WHT	N/C
SHIELD	OPEN



REFERENCE SPECIFICATIONS

ELECTRICAL

- Excitation Voltage: 9 to 36 Vdc
- Output Signal: 4-20 mA
- Circuit Protection: Short circuit or reversed wired – Indefinite
- Load Resistance: 1400 Ω max. at 40 Vdc excitation
- Response Time: ≤5 ms to 90%
- Connection: Hytrel jacketed, 4-conductor, 18 AWG with vent tube and hydrophobic filter, 8' long, other lengths available.

MATERIALS OF CONSTRUCTION

- Housing: 316L stainless steel, optional titanium
- Pressure Cavity: 316L stainless steel

STATIC ACCURACY (RSS) (HYSTERESIS, NON-LINEARITY & REPEATABILITY @ +70 °F)

Standard: ±0.5% FSO, ±0.2% FSO, and ±0.1% FSO

MECHANICAL

- Zero Balance and FSO: ±1.0% FSO @ +70 °F
- Process Connection: PVC bullet nose
- External Pressure: Rated to 900 ft WC (274 meters) max.
- Proof Pressure: 2X FSO
- Burst Pressure: 4X FSO
- Approximate Weight: 10 oz (0.3 kg) nominal, options may increase weight
- Diameter: 0.875" (2.22 cm)

PRESSURE RANGES

- 0-20" WC thru 300 PSI (50 MBAR to 21 BAR)

THERMAL SPECIFICATIONS

- Compensated: 0 °F to +140 °F (-32 °C to +60 °C)
- Operating: -40 °F to +185 °F (-40 °C to +85 °C)
- Storage: -40 °F to +195 °F (-40 °C to +90.6 °C)
- Effect on Zero/Span: <±2.0% FSO/100 °F

**Standard configurations shown.
Please consult factory for other options.**

All specifications are for reference purposes only. In the interests of continuous product improvement, all specifications are subject to change without notice. Please contact GP:50 for assistance with your application.

© 2014 GP:50 NY Ltd. | U.K. Distributor Interface Force Measurements Ltd

Tel: 01344 776666 Fax: 01344 774765 Email: info@interface.uk.com Web: www.gp50.co.uk

